

BLUEBIRD EF 500 iBio

The Proven Innovation of Enterprise Mobility



Durable and Scratch Resistant

EF500 iBio's compact, lightweight design incorporates Bluebird's proprietary TankSmith™ technology. The 5-inch high definition multi-touch display is exceptionally resistant to scratches and deep chips.

Ergonomic, Single-handed Operation

With a weight of only 302 grams, EF500 iBio is ergonomically designed for comfortable single-handed operation.

1D and 2D Scanning

The built-in bar code scanner rapidly reads 1-D and 2-D bar codes and it also has a 8 MP camera for taking pictures and capturing signatures.

Full Voice Capabilities with Push to Talk

EF500 iBio comes with full voice capabilities; including noise cancelling, speakerphone, and push to talk that enable more efficient communication among employees, whether it is one-to-one or one-to-many.

Efficient Power Management

EF500 iBio uses several power saving technologies to ensure it will run for the entire work shift.





Specifications

Description	Parameters
PERFORMANCE CHARACTERISTICS	
CPU	Quad Core Processor 1.2GHz
OS	Android 6.1
MEMORY	2GB RAM/16GB Internal Memory
INTERFACE	Docking connector; 1 microUSB port
COMMUNICATION OPTIONS	
WWAN RADIO	LTE/HSPA+/HSPA/UMTS, EDGE/GSM/GPRS
WLAN RADIO	802.11 a/b/g/n/d/h/i
WPAN RADIO	Bluetooth Support
DATA CAPTURE	
RFID	ISO 15693 13.56 MHz Compa ble standards:
	ISO/IEC14443-4 Type A & B, MIFARE (Classic 1K and 4K , DESFire, MIFARE Plus),
	NFC Forum (tag type 1, 2 , 3, 4)
CAMERA	8Mega Pixel Auto Focus Camera with LED Flash;
BARCODE SCANNER	The built-in imager 1D / 2D
PHYSICAL CHARACTERISTICS	
DIMENSIONS	203.7 x 82.3 x 21.05 mm
WEIGHT	302g
Display & Touch	5-inch Display
Battery	User replaceable Battery
	Standard: 3.8V, 3200 mAh / Extended: 3.8V, 6400 mAh
EXPANSION SLOT	Customer-accessible MicroSD
SIM/SAM SLOT	1 SIM (WWAN Only)
AUDIO	VoWWAN; VoWLAN; PTT ready; Dual Microphone with Noise Cancellation, Stereo Ear jack [(3.5mm),
	Speaker Available
GPS	Integrated A-GPS, GLONASS
Sensors	Ambient light, Proximity, Gyroscope, Accelerometer, Magnetic
USER ENVIRONMENT CHARACTERISTICS	
DURABILITY	TankSmith™ Technology; IP65 Sealing, 1.5m Drop
	MIL-STD 810G Method 501.5 / 502.5 / 507.5 /516.6 /514.6 /503.5
OPERATING TEMP	-20°C to 60°C



BACHDUY TECHNOLOGY CO., Ltd.,
Address: 676/13 Le Quang Dinh Str., Ward 1, Dist Go Vap, HCMC
Website: www.bachduy.com
Email: doanle@bachduy.com Phone: (+84) 908 867 674
Bank Account: 2034 85 179 - ACB Phan Van Tri Branch, Tax code; 0313 121 940

STORAGE TEMP	-25°C to 70°C
HUMIDITY	95% non-condensing
FINGERPRINT SCANNER	
CERTIFICATIONS	FIPS PIV IQS / ISO 19794-4 : 2011 , MINEX & FIPS 201 complaint algorithms, STQC, Fake Finger Detetion
SECURITY	FIPS 140-2 Level 2, Data is encrypted
SENSOR TYPE	OPTICAL – CBM-E3, MSO 1300 E3 Morpho
FEATURE EXTRACTION	Propetary, ISO 19794-2, ANSI 378
FAKE FINGER DETECTION	Fake Finger Detetion
ACCESSORIES	
CRADLE (1 SLOT)	1 Device Charging , Includes 1 Spare Battery Charging. Adaptor 9V / 3A
CRADLE (4 SLOTS)	4 Device Charging , Includes 4 Spare Battery Charging. Adaptor 9V /10A
USB CHARGER	Micro USB cable, 5V / 2A
VEHICLE CHARGER	Vehicle Mount Charger 5V / 2A , Vehicle Holder
ETC.	Stylus Pen, Hand Strap, Cover Pouch