



BACHDUY TECHNOLOGY CO., Ltd.,
 Address: 676/13 Le Quang Dinh Str., Ward 1, Dist Go Vap, HCMC
 Website: www.bachduy.com
 Email: doanle@bachduy.com Phone: (+84) 908 867 674
 Bank Account: 2034 85 179 - ACB Phan Van Tri Branch, Tax code; 0313 121 940

MOBILE THERMAL TRANSFER LABEL PRINTER



Thermal transfer ribbon for label printing

Thermal transfer technology achieves excellent label printing effect and longer storage period. (At least 10 years, depends on label materials); Unique ribbon with anti-counterfeit chip, ensures the high quality of products and the protection of benefits for partners and customers.

Mini and portable, easy to carry

The size is 211×111×79mm only, light and handy, easy to carry without any limits.

Powerful and user-friendly label editing APP

Perfectly support Bar code and QR Code printing, complies with international standards; Easy to import Excel tables for bulk printing; Support multiple printing contents: symbols, pictures, logo, graphics, etc. High-speed printing improves working efficiency.

Provide various platforms and user-friendly interfaces

Provide multiple interfaces for Android, iOS, Windows, Web, etc. Make the integration of customer manage system more easy; Support common explorers, like IE, Chrome, Firefox, etc

Various optional accessories, strong functional upgrading

Optional 300DPI resolution of print head for legible printing;
 Optional Wi-Fi module for more flexibility of connectivity;
UHF RFID module simultaneously prints contents both from label displayed and RFID chip.

OLED display demonstrates printer status clearly

With spontaneous OLED display, the printer status is clearly demonstrated, adapt easily to different working conditions.

Multiple connection modes

Support Bluetooth connecting to Android and iOS phones/PAD, USB connecting to PC, Android phone/PAD; Auxiliary NFC supports Bluetooth in quick pairing and connecting; Fully compatible with various smart phones, PAD, PC and special-purpose terminals for connecting and printing



Applications:



Cable Label




DDF Shelf Label



Flag-shaped Label



Fixed Assets Label



State GRID Label



Colorful Price Label



Jewelry Label



Customized Ribbon



Customized Label



BACHDUY TECHNOLOGY CO., Ltd.,
Address: 676/13 Le Quang Dinh Str., Ward 1, Dist Go Vap, HCMC
Website: www.bachduy.com
Email: doanle@bachduy.com Phone: (+84) 908 867 674
Bank Account: 2034 85 179 - ACB Phan Van Tri Branch, Tax code; 0313 121 940

Specifications	
Description	Parameters
Display Type	OLED display
Print Method	Thermal transfer line
Print Color	Black and white
Resolution	203 dpi/300 dpi (optional)
Dot per Line	384 dots/line
Print Speed	15 ~ 30mm/s
Lifecycle Time	260 ~ 300m (12.5% print density)
Standby Time	About 5 years (power off)
Battery Capacity	2600 mAh
Charge Mode	5V USB
Charge Time	6 ~ 7h
Power Bank Function	Support
Roll Paper Type	Self-adhesive paper
Paper Size	54(W) × dia.50 (mm)
Print Width	48mm
Paper thickness	0.05 ~ 0.15 mm
Dimension	211(L) × 111(W) × 79(H)mm
Standard Accessories	Power adaptor, battery, optional ribbon, USB cable
IP standard	IP54
Operating Temperature	0°C ~ 45°C
Interface	Micro USB, Bluetooth (Android, iOS), 2.4G Wi-Fi (optional)
Command Set	LPAPI®, ESC/POS compatible with instruction sets
Location Mode	Reflection-Type
Self-check Function	Cover open, paper out, low battery, overtemperature
Print Contents	* Text, picture, line, graphics * 1D Barcode: CODE39, CODE128, EAN, UPC, other commonly used barcodes * 2D Barcode: QRCode, PDF417, DataMatrix
RFID Print	UHF 900MHz, compatible with ISO18000-6C/EPC Gen2 (optional)