












Enterprise Mobile Computer

VX500

Rugged Smart Handheld With Integrated RFID Reader

Rapid work process through the latest OS and powerful CPU
 Increase work efficiency with powerful RFID reader module
 Powerful durability in the harshest environments
 Quick data capture through high performing barcode scanner
 Long-lasting battery power



 OS Android 10	 Performance Octa-Core Processor	 Wireless Wi-Fi, Bluetooth	 Battery User Replaceable, Smart Battery	 Scanning 1D & 2D imager	 RFID Short Range
 Sealing IP68	 Operation Temp -20°C to 55°C -4°F to 131°F	 Camera 13MP Autofocus with flash	 Display 5" HD (1280 x 720)	 Drop Resistance 1.5m/4.9ft. MIL-STD-810G 1.8m/5.9ft. MIL-STD-810G (w Rugged Boot)	

Key Features

Best in enterprise-class Qualcomm Snapdragon™ CPU (2.2GHz, Octa-Core) and Android 10 OS increase work efficiency, supporting users' work process in prompt and stable ways. Users can switch their apps on the display quickly by Universal Flash Storage (UFS) memory which increases the speed of operation.

Increase work efficiency with powerful RFID reader for high precision Up to 300 tags/sec of reading rate with high precision and nominal reading distance can maximize your work efficiency up to the fullest. Suitable to use in retail, healthcare, logistics, manufacturing and other verticals.

Powerful durability in the harshest environments Usability-proven in touch and harsh environments Bluebird TankSmith® Technology and Corning® Gorilla® Glass enhance durability of the device meeting

1.8m of drop spec MIL-STD 810 (with Rugged Boot) and IP68 Sealing rate. VX500 provides flexible multi-touch including glove, wet, and stylus as well as the best outdoor readability that you can see the display under the very bright sunlight.

High performance barcode scanner for quick data capture The latest scan engine provides superior wide range up to 24-inch/60cm for 1D/2D barcodes, labels, and documents. Workers can scan even poor quality, damaged and dirty barcodes. It delivers lightning fast barcode scan with motion tolerance providing fast scan on pressing the scan button. Large sweet spot makes workers can scan easily with point-and-shoot simplicity.

Long-lasting battery power (Hotswap support) User replaceable battery with high capacity of 4350mAh gets you free from worrying about re-charge. As hotswappable battery it supports work continuity even when unexpectedly detached and prevents data loss. With Bluebird BOS™ (Business Optimizing Solution) Power Manager solution, it enables to manage battery life status which delivers replacement period for aged batteries.

Mobile device management software eco-system BOS™ (Business Optimizing Solution) Bluebird BOS

※ Product design is subject to change.

Verticals & Applications

Retail

- Price/Inventory Check
- Inventory management
- mPOS (Mobile POS)
- BOPIS (Buy online, Pick up in store)
- Loyalty management
- Sales assistance
- Voice communication
- Electronic coupon
- Coupon verification

Field Service

- Asset management
- Invoicing


BOS™ (Business Optimizing Solutions) provides various features optimized for use of enterprise device from app development, device deployment, to business performance management as an integrated solutions system. With BOS™ you can implement integrated management for VX500 in an efficient way.

Specification

PERFORMANCE CHARACTERISTICS

CPU	Qualcomm Snapdragon™ 2.2 GHz Octa Core Processor (SD660)
OS	Android 10 upgradeable to Android 14
Memory	4GB RAM / 64GB Flash (UFS)

PHYSICAL CHARACTERISTICS

Dimension (L x W x D)	158.3 x 75.8 x 14.9mm
Weight	286 g
Display	5.0" HD (1280 x 720), TFT-IPS
Touch panel	Capacitive multi-touch (Stylus, Glove, Wet)
Backlight	LED backlight
Power	User Replaceable 3.85V / 4350 mAh  BOS™ Power manager station support, preventing downtime through battery life management and battery status
Hotswap	Support
Quick Charging	Fast charging
Expansion Slot	Up to 128GB MicroSD
SIM / SAM	Hybrid Dual SIM Slot (2 Nano SIM or 1 Nano SIM/1 Micro SD) - 1 Nano SIM is supported by micro SD Card Slot Single SAM (Optional)
Interface	USB Type C Connector (USB 2.0) Docking Connector (Charging)
Notification	Audible tone; multi-color LEDs; vibration
Keypad & Button	Power Button; Volume up/down Buttons; Home, Back, Menu Buttons; PTT Hot Key support - Available dual-action side scan triggers
Voice & Audio	High-quality dual speakers 2W (2Wx1) Dual noise-cancelling microphones; 3.5mm headset jack

Network

WWAN (WWAN SKU Only)	Korea : -LTE : B1(2100MHz), B3(1800MHz), B5(850MHz), B7(2600MHz), B8(900MHz), B28R(700MHz) -WCDMA : B1(2100MHz) Worldwide : - LTE FDD : B1(2100MHz), B2(1900MHz), B3/B9(1800MHz), B4(1700/2100MHz), 5/26/18/19(850MHz), B7(2600MHz), B8(900MHz), B20(800MHz), B28(700MHz) - WCDMA : B1, B2, B4, B5, B8, B9, B19
GPS	A-GPS, GLOASS, BEIDOU, Galileo

WLAN

Band	IEEE 802.11 a/b/g/n/ac/d/h/i/k/r/w IPv4, IPv6, 2x2 MU-MIMO (WiFi SKU) 1x1 SISO (WWAN SKU)
-------------	---

WPA

Bluetooth	Bluetooth v5.0, BLE Class 2
------------------	-----------------------------

DATA CAPTUR

Barcode	1D & 2D Laser
Camera	Rear – 13MP Autofocus with flash Front – 5MP fixed
NFC	UHF RFID (Nominal read range: up to 1m)
Biometrics	Fingerprint (via Home button) (Optional)

SENSOR

Light Sensor	Ambient Sensor
Motion Sensor	Proximity, Accelerometer, E-Compass, Gyro, Barometer

USER ENVIRONMENT

Operating Temp.	20°C to 55°C / 4°F to 131°F
Storage Temp.	30°C to +70°C /-22°F to +158°F
Humidity	95% non-condensing
Drop Spec	1.5m MIL-STD-810G 1.8m(5.9ft.) MIL-STD-810G; Multiple 1.8m(5.9ft.) drops on concrete at room temperature with the rugged boot accessory
Sealing	IP68
Tumble Spec	300 1.6 ft./0.5m tumbles; meets and exceeds IEC tumble specification
Vibration	4G peak, 5 Hz to 2 kHz, 1 hour duration per axis
Thermal Shock	-40° C to 70° C / -40° F to 158° F rapid transition 10 cycles (1 cycle = 1.25 hours at -40°C and 1.25 hours at 70°C)
Electrostatic Discharge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge

ACCESSORIES

Accessories	1) 1 or 4 slot charging cradle (Includes a bay for Spare Battery Charging.) 2) 1 or 4 slot ethernet cradle (Includes a bay for Spare Battery Charging.) 3) Handstrap 4) Protective Flim
--------------------	--

※ Specifications are subject to change without notice.